

400D+400H

12" Dual Printheads DTF Printer



Product Application



Wide applications in Apply to nylon, chemical fiber, cotton, leather, diving suit, PVC, EVA, etc.

• Equipment Parameter

12" Dual Printheads DTF Printer

Model	400D
Printhead and Quantity	I3200-A1/L1600-A1/XP600 2pcs
Printing Speed	6 Pass 3m ² /h 8 Pass 2m ² /h
Printing Width	0-335mm
Media Type	Pet film
RIP Software	Standard with Printfactory, Maintop, PhotoPrint, CADlink for Optional
Temperature/Humidity	Temperature:20-30°C Humidity:45-65%
Power/Voltage	50HZ/60HZ, 220V/110V 10A
Machine Dimension	L950xW600xH400mm
Package Dimension	L1040xW600xH650mm
Net Weight	50KG
Gross Weight	80KG

Tunnel type Shaking and color Fixing Machine

Model	400H
Applicable Medium	Nylon, chemical fibercotton, leather, diving suit, PVC, EVA, etc.
Retractable Media Width	0-350mm
Fan Control	Shake powder control, dusting control, direction and quantity control
Rewinding Function	Automatic induction winding
Material Delivery Method	Normal transmesion
Heating and Drying Function	Efficient drying and curing
Rated Voltage	110V/220V
Rated Current	5A
Rated Power	950KW
Energy Consumption	500KW
Machine Dimension	L950xW540xH560mm
Package Dimension	L760xW560xH620mm
Net Weight	30KG
Gross Weight	60KG